## Hot Spot<sup>®</sup> Spas

## ТΧ



TX shown with Pearl shell



TX shown with Pearl shell/ Espresso cabinet

HOT SPOT	
	)

Seating Capacity	2 adults
Dimensions	5'8.5" x 5'8.5" x 29"H/1.74m x 1.74m x .74m
Water Capacity	140 gallons/530 litres
Weight	526 lbs./239 kg dry; 2.044 lbs./927 kg filled*
Spa Shell Options	Pearl, Sand
Cabinet Options	Coastal Gray, Espresso, Redwood
Jets - 10	1 Moto-Massage' jet 16 Directional Precision' jets 8 Directional Precision' jets
Waterfall	n/a
Jet Pump 1	Wavemaster <sup>®</sup> 4000; Two-speed, 1.0 HP Continuous Duty, 1.7 HP Breakdown Torque
Jet Pump 2	n/a
Circulation Pump (Optional)	SilentFlo 5000°
Ozone System (Optional)	FreshWater <sup>®</sup> III Corona Discharge
Control System	IQ 2020 <sup>°</sup> 115v/20 amp <sup>**</sup> (Includes G.F.C.I. protected power cord) or 115v/30amp <sup>***</sup> or 220v/50amp <sup>***</sup> , 60Hz
Lighting	Blue LED light, dimmable; Splendors <sup>*</sup> multi-colored LED light, dimmable (optional)
Heater	No-Fault <sup>*</sup> 1000w/115v
Energy Efficiency	FiberCor <sup>°</sup> Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
Effective Filtration Area	30 sq. ft., top loading
Vinyl Cover	3" to 2" tapered, 1 lb. density foam core Ash, Espresso or Rust
Cover Lifter (Optional)	n/a
Steps (Optional)	Everwood <sup>®</sup> or Polymer Coastal Gray, Espresso or Redwood
Entertainment (Optional)	Wireless Sound System

Includes water and 2 adults weighing 175 lbs. each
Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.
G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode. Export models available in 230v, 50Hz, 1000w Heater

From the makers of

