## **JETSETTER**<sup>®</sup>



Jetsetter shown with Platinum shell



Jetsetter shown with Platinum shell / Monterey Gray cabinet



Seating Capacity	3 adults
Dimensions	7' x 5'5" x 29"/2.13m x 1.65m x .74m
Water Capacity	225 gallons/852 liters
Weight	475 lbs./215 kg dry; 2,877 lbs./1,305 kg filled*
Spa Shell Options	Alpine White, Crème, Ice Gray, Platinum, Tuscan Sun or Desert*
Cabinet Options	Everwood HD: Mocha, Monterey Gray or Teak**
Jets - 14 (w/ Stainless Steel Trim)	1 Moto-Massage <sup>°</sup> DX jet (2) 1 JetStream <sup>°</sup> jet 2 Rotary Hydromessage jets 1 Directional Hydromassage jet 4 HydroStream <sup>°</sup> jets 4 Directional Precision <sup>°</sup> jets
Water Care System (Optional)	ACE" Salt Water Sanitizing System or EverFresh" System
Jet Pump	Wavemaster <sup>*</sup> 7000; One-speed, 1.65 HP Continuous Duty, 3.5 HP Breakdown Torque
Circulation Pump	SilentFlo 5000° for quiet, continuous filtration
Effective Filtration Area	90 sq. ft., top loading 100% no-bypass filtration
Ozone System	FreshWater <sup>®</sup> III Corona Discharge
Control System	IQ 2020' with LCD control panel 115v/20 amp (includes G.F.C.I. protected power cord) or 230v/50amp, 60 Hz***
Lighting System	Luminescence' multi-color four-zone
Heater	No-Fault <sup>°</sup> , 1500w/115v or 6000w/230v
Energy Efficiency	Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
Vinyl Cover	3.5" to 2.5" tapered, 1.5 lb. density foam core, with hinge seal in Caramel, Chocolate, Slate, or Evergreen
Cover Lifter (Optional)	CoverCradle <sup>*</sup> , CoverCradle II, Lift 'n Glide <sup>*</sup> or UpRite <sup>*</sup>
Steps (Optional)	Everwood <sup>®</sup> HD, NXT, or Polymer

Entertainment System (Optional) Wireless Sound System

\* Includes water and 3 adults weighing 175 lbs. each

\*\*Some color combinations are considered special orders. Ice Gray/Teak, Crème/Monterey Gray, Desert/Monterey Gray and Platinum/Teak have special order pricing. See your dealer for details. \*\*\*G.F.C.I. Protected sub-panel required in 230v mode Export models available in 230v, 50Hz, 1500w Heater, 2.5 HP, Tri-X\* filters